



ATTIX 19 AE FLOOD SUCKER

Ultimate Sump Pump Vacuum

Collect and discharge nearly one gallon of water per second with the ATTIX 19 AE Flood Sucker. It is the ideal solution for flood restoration companies, abatement contractors, fire departments and municipalities.

The ATTIX Flood Sucker separates solids into a stainless-steel basket inside the canister while liquids are simultaneously discharged through a fire hose. The powerful discharge pump expels water up to 30 feet vertically and 150 feet horizontally. It can be operated in three modes—vacuum only, pump only, or vacuum and pump.

Where ordinary sump pumps leave up to 1.5 inches of liquid on the ground, the Flood Sucker completely removes liquids, leaving a dry surface behind.

Standard Features:

- Accessory Storage
- On-board Power Receptacle
- Rubber Cable with Wrap Hook
- Soft Start
- Tool Deposit
- Power Regulator

TECHNICAL DATA

ATTIX 19 AE

Part Number	M60004
Voltage @ 60 Hz. (V)	120
Power @ 60 Hz. (W)	1000
Air Flow, max. (CFM)	140
Waterlift, max. (in. H ₂ O)	105
Noise Level (dB(A)) @ working distance of 3 m.	57
Container Capacity (gal./L)	19/72
L x W x H (in.)	24 x 23 x 38
Shipping Weight (lbs.)	97
STANDARD ACCESSORIES	
Hose (dia. x L) (in. x ft.)	1.5 x 13 (Part # 15365)
Discharge Hose, PVC lay-flat (L) (ft.)	25 (Part # 100088)
Curved Wand, stainless steel	(Part # 302000447)
Extension Tube (2 Piece), stainless steel	(Part # 15546)
Tube Holder	(Part # 60609)
Industrial Squeegee	(Part # 5149)



*Photo courtesy of Ultimate Garage

Nilfisk Advance, Inc.
Industrial Vacuum Division
740 Hemlock Rd., Suite 100
Morgantown, PA 19543

Phone: (800) 645-3475
Fax: (610) 286-7350
Email: questions@nilfisk.com
Website: www.nilfiskaltovacuum.com

Nilfisk
ALTO
works for you