



AaquaTools
water driven products & solutions

industrial & solid waste



Advanced Ozone Delivery System

C1 MOBILE DISINFECTION CART

Keep Your Public Spaces Clean & Safe

The AaquaTools C1 Mobile Ozone Generator/Disinfection System is a safe organic solution that can replace traditional or harsh chemical disinfection products. Ozone has been used for more than a century as an effective way to manage bacteria, viruses, fungi, and protozoa, in water treatment applications. Its effectiveness is the basis for its increasing use in cleaning and disinfection in cities worldwide.

Schools, parks, public transport, restrooms, public buildings, or anywhere there's constant contact with people, whether they are showing signs of illness or not, can be sanitized in this way.

- Precision welded stainless steel frame
- Small foot print
- Engineered with center of gravity in mind for easy, stable maneuverability
- Convenient work basket with built in drain
- Oxygen and ozone gas features standard
- 12V control panel
- Manufactured in California wine country



WWW.AAQUATOOLS.COM

Specifications

Power	110 VAC 60 Hz, 12A; 220/240 VAC 50/60 Hz, 7A
Ozone Gas Output	18 g/hr @ 12 scfh oxygen, 4% by weight
Oxygen Gas Output	90 ±% @ 15 scfh
Water Inlet	50-80 psi
Ozone Water Output	8.0 ppm @ 10 gpm
Temperature	50-100°F
Supply Connections	Water inlet hose Tri-clover or 3/4" FNPT; dissolved ozone/water outlet Tri-clover or 3/4" FNPT
Power Cord	10 feet
Material	Stainless steel
Dimensions	54.3"H x 20.6"W x 26.3"D
Weight	160 lbs

Ordering Information

MSW400	C1 - Mobile Disinfection Cart
FTS614	SS Fitting - TC clamp 1.5"
FTS612	SS Fitting - TC 1.5" x 3/4" mpt
FTS613	SS Fitting - Camlock 3/4" female x 3/4" mpt
FTB426	Brass Fitting - garden hose female x 3/4" mpt
GAS40	Gasket - TC 1.5", epdm
HA400	25' Ozone Hose Assembly, 3/4" hose, tc 1.5 In ss fittings
HA401	50' Ozone Hose Assembly, 3/4" hose, tc 1.5 In ss fittings
HA402	50' Ozone Hose Assembly, 3/4" hose, camlock 3/4 in ss female fittings
HA403	25' Ozone Hose Assembly, 3/4" hose, Camlock 3/4" SS female fittings
HA420	Ozone Delivery Line - Teflon 1/4" OD, 50' with coupler
BGA40	Barrel Gas Assembly - ozone bung w/destruct, 50' Teflon tubing
BGA41	Barrel Gas Assembly - ozone daisy-chain bung
CMT809	Ambient Ozone Monitor - 200 0-0.5 ppm, handheld, LCD display
CMT931	Ambient Ozone Monitor (built-in), 0-0.5 ppm
CMT910	ORP Controller (built-in), LCD display, ph, temp
CMT540	Ozone PPM Controller (built-in), LCD display, temp
TK20	Test kit- Ozone Colormetric DPD 0-2 ppm, 30A
RESP01	Respirator mask - carbon filter, 10 pk

Our C1 Mobile Disinfection Cart provides ozone enriched water for surface disinfection. Built to last with reliable state-of-the-art on-board technology, and powerful top-of-the-line components. Wash down floors, walls and equipment; rinse barrels and tanks with the push of a button and be assured that you receive the ozone you need to get the job done.

Easy to maneuver, the cart replaces traditional hot water and harsh chemicals with safe disinfection on contact.

The Mobile Cart is best when you require ozone disinfection in multiple locations within a facility, different buildings, larger facilities, or when you simply want the convenience of mobility.

The C1 mobile disinfection cart comes standard with a separately controlled ozone gassing feature. This supply of ozone gas offers you greater disinfection options and is typically used to gas and preserve stored barrels instead of Sulfur Dioxide.

In addition to ozonated water, ozone gas will help disinfect sealed containers or tanks, and work as a part of your environmental disinfection protocol. Further, the mobile cart comes standard with a separately controlled oxygen gas feature useful in micro-oxy applications.

Special Features

- Easy to use push button controls – full system monitoring indicators
- Microprocessor-controlled ozone system with built-in soft start and self-diagnostics
- Rotary vane booster pump – boosts low pressure water supplies for better coverage
- Ozone production up to 18 grams/hour via gas outlet
- Typical ozone dosage rate is 8.0 ppm at 10 gpm
- Separately controlled ozone and oxygen gas outlet
- Built-in oxygen concentrator delivering 93% oxygen at 15 scfh
- 3/4 fnpt inlet (optional front or back location) and outlet
- Stainless steel welded tubing frame and water safe exterior
- Built-in tool basket
- Designed for easy service access or maintenance
- Critical parts are fully-contained for water safe operation
- Designed with low center of gravity, well-balanced and a small footprint
- Ozone/oxygen gas flow meter

Options

- Water hoses
- Barrel washers
- Tri-clover fittings
- ORP monitor
- Dissolved O3 monitor
- Ambient ozone monitor
- Dissolved ozone test kit



P/N C1-Ozone-Cart-2020 - 01/20
© 2020 AaquaTools, Inc. – All rights reserved.
Specifications are subject to change without notice.



Direct: 916.635.2922
Fax: 916.635.8856
info@aaquatools.com
www.aaquatools.com