# naintenance solutions



# **HIGH FLOW SERIES**

# **Electric Stationary Belt Drive Cold Water Pressure Washers**

# **Pressure Washers Optimized For AaquaTools Cleaning Heads**

Our High Flow line of stationary pressure washers are constructed of stainless-steel to resist rust and corrosion, making them the perfect solution for wash bays to clean vehicles and equipment. Industrial facility owners use it to keep floors and workables clean and sanitized.

## **Unit Includes:**

- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off

# **Pressure Washer Standard Features Include:**

- Auto Stop/Start
- Able to receive hot water up to 180°





# **High Flow Series**

# **Cold Water - Electric - Stationary - Belt Drive**

# **Pressure Washers Optimized For AaquaTools Cleaning Heads**

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	DIMENSIONS (LXWXH)	NET WEIGHT
HF-2004-WSE2G	1800	6	8 HP 230/1	29.5x20.5x15in	214 lb.
HF-2004-WSE2G	1500	5.5	6 HP 230/1	29.5x20.5x15in	214 lb.
HF-3004-WSE3G	2750	5.6	10 HP 208/3	29.5x20.5x15in	234 lb.
HF-3004-WSE3G	2500	5.6	10 HP 460/3	29.5x20.5x15in	234 lb.
HF-3004-WSE3G	1500	10.0	10 HP 230/3	29.5x20.5x15in	234 lb.

## OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0069	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	All models
CX-0076	460V on 6.0-HP, 3-phase model - For when you have 460V of power available	HF-2004-WSE3G
CX-0077	460V on 8.0-HP, 3-phase model - For when you have 460V of power available	HF-3004-WSE3G
CX-0078	Remote box - Adds control box which may be mounted away from unit to control on/off	All models
CX-0096	Hour meter - Displays the number of hours unit has been in operation	All models
CX-0109	Additional remotes (up to 3) - Additional remotes that may be added to unit after the first remote is installed	All models

### ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
AW-9501-0000	Stainless-steel wall mounting bracket - Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0000	Powder coated steel wall mounting bracket - Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0001	Powder coated steel floor stand - Provides a permanent location for your pressure washer in a shop or plant facility	All models



20-amp plug







NEMA L15-20P, 20-amp plug

, NEMA L15-30P 30-amp plug

## Pump:

- Belt drive triplex piston General pump with ceramic plungers
- Forged brass manifold
- Thermal relief valve
- Pump accepts incoming water up to 180°F
- Quick connect low pressure detergent injector

# Frame:

- Stainless-steel cabinet design with removable panel
- Four rubber isolators







MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

# Motor:

- Totally enclosed fan-cooled electric motor with manual thermal overload protection (2000-PSI models)
- Open drip-proof electric motor (1000 and 3000-PSI models)
- 4-foot power cord with GFCI

# **Component:**

Time delay shutdown
Auto Stop/Start

# **Unit Includes:**

- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off

P/N HighFlowSeriesPressureWashersCold-2021 - 04/21 © 2021 AaquaTools, Inc. – All rights reserved. Specifications are subject to change without notice.





Direct: 916.635.2922 Fax: 916.635.8856 info@aaquatools.com www.aaquatools.com